

**CONSTRUCTION PRODUCTS REGULATION.**  
**DECLARATION OF PERFORMANCE**

No...1..... CPR 07-2013

- 1 Identification code: Insulating Glass Unit
- 2 Serial number: Annealed Glass
- 3 Intended use. Glass in building & construction
- 4 Manufacturer: J.D. Glass, Unit 5, The Shades Ind. Park,  
Soham, Ely, Cambridgeshire. CB7 5DE
- 5 Authorised representative: Not applicable
- 6 Assessment and verification of constancy performance: System 3
- 7 Relevant harmonised standard: EN1279-5:2005+A2:2010

BSI NB 0086 carried out Part 2 Type Test and issued report no. 262/7031708  
TUV Rheinland NB 0336 & 1750 carried out Part 3 Gas Leakage Test and issued  
Report No.....

- 8 European Technical Assessment: Not applicable.

9 Declared Performance

Essential Requirement	Declared performance	Harmonised standard
Resistance to fire	NPD	EN 1279-5: 2005+A2:2010
Reaction to Fire	NPD	
Bullet Resistance	NPD	
Explosian Resistance	NPD	
Burglar Resistance	NPD	
Pendulum body impact	NPD	
Mechanical resistance		
Temperature	NPD	
Imposedload	NPD	
Radiation Performance. Solar	NPD	
Light tansmittance	NPD	
Thermal performance	1.7 W/(m2.K) <	

Specific Technical Documentation: Not applicable.

- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of J.D. Glass

Date 05/06/2013

Managing Director.



**CONSTRUCTION PRODUCTS REGULATION.**  
**DECLARATION OF PERFORMANCE**

No...2..... CPR 07-2013

- 1 Identification code: Insulating Glass Unit
- 2 Serial number: Toughened Glass
- 3 Intended use. Glass in building & construction
- 4 Manufacturer: J.D. Glass, Unit 5, The Shades Ind. Park,  
Soham, Ely, Cambridgeshire. CB7 5DE
- 5 Authorised representative: Not applicable
- 6 Assessment and verification of constancy performance: System 3
- 7 Relevant harmonised standard: EN1279-5:2005+A2:2010
- BSI NB 0086 performed Part 2 Type Test and issued report numbe 262/7031708

8 European Technical Assessment: Not applicable.

9 Declared Performance

Essential Requirement	Declared performance	Harmonised standard
Resistance to fire	NPD	EN 1279-5: 2005+A2:2010
Reaction to Fire	NPD	
Bullet Resistance	NPD	
Explosian Resistance	NPD	
Burglar Resistance	NPD	
Pendulum body impact	1 (C) 3	
Mechanical resistance		
Temperature	NPD	
Imposedload	NPD	
Radiation Performance. Solar	NPD	
Light tansmittance	NPD	
Thermal performance	1.7 W/(m2.K) <	

Specific Technical Documentation: Not applicable.

- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of J.D.Glass

Date 05/06/2013

Managing Director.





13

J D glass, Unit 5, The Shades Ind. Park, Soham,  
Ely, Cambridgeshire, CB7 5DE

Insulating Glass Unit - Annealed glass

No. 0001 CPR 07-2013

Essential Characteristics.	Declared Performance	Harmonised Standard.
Pendulum body impact resistance	NPD	EN1279-5 +A2:2010
Thermal Performance	1.7 W/(m2.K) <	
Type Testing conducted by NB 0086 Intended for use: Energy conservation and noise reduction.		



13

J D Glass, Unit 5, The Shades Ind. Park, Soham,  
Ely, Cambridgeshire. CB7 5DE

Insulating Glass Unit - Toughened Glass

No. 0002 CPR 07-2013

Essential Characteristics.	Declared Performance	Harmonised Standard.
Pendulum body impact resistance	1 ( C ) 3	EN1279-5 +A2:2010
Thermal Performance	1.7 W/(m2.K) <	
Type Testing conducted by NB 0086 Intended for use: Energy conservation and noise reduction.		